



ILLUMIVUE™ BY MSTR

## 5MP IP PTZ Camera with NightLight and NightColor

IP5PTZ-NL

SKU: 174215    UPC: 81993201292

Introducing the Illumivue IP5PTZ-NL 5MP IP PTZ Camera with NightLight and NightColor, a powerful and versatile surveillance solution that brings exceptional image quality, advanced functionality, and enhanced night vision capabilities to safeguard your surroundings. With its cutting-edge technology and intelligent features, this camera redefines the boundaries of surveillance systems.

The IP5PTZ-NL captures incredibly sharp and detailed images, ensuring that every critical aspect is captured with precision. Whether monitoring a wide area or focusing on specific points of interest, this camera delivers outstanding visual clarity, providing crystal-clear footage.

The IP5PTZ-NL features NightLight technology, which features two bright LED lights and extra-large aperture that greatly improves the camera image in near-dark situations while deterring criminals.. The built-in LEDs illuminate the scene with both infrared and white light, allowing for enhanced visibility in low-light conditions. This innovative feature ensures that you capture detailed and accurate images even in complete darkness, providing you with 24/7 surveillance coverage.

Additionally, the IP5PTZ-NL incorporates NightColor technology, enabling you to see vivid and accurate colors even in low-light conditions. No more sacrificing image quality during nighttime surveillance. NightColor preserves the integrity of colors, providing you with true-to-life visuals and enhancing your ability to identify objects and individuals, making surveillance more effective and reliable.

The Illumivue IP5PTZ-NL 5MP IP PTZ Camera with NightLight and NightColor is a versatile and powerful security solution. Its exceptional image resolution, innovative NightLight and NightColor technologies, PTZ functionality, and intelligent alerts make it the perfect choice for those seeking advanced surveillance capabilities.


### Features

- 5MP IP Pan, Tilt and Zoom (PTZ) Camera
- 4x optical zoom (2.8 ~ 12mm) @ F1.6 Lens
- 120DB True WDR - Wide Dynamic Range for scenes with high-contrast lighting
- NightColor - Ensures ultra-high image quality in low illumination environment
- NightLight - Greatly improves the camera image in near-dark situations
- 164ft (50m) IR Range
- Advanced Analytics - Supports line cross, intrusion, enter area, leave area, face detection, face capture, auto tracking, motion, tampering & audio detection
- Active Defender - Can warn intruders with flashing white light strobe lights and audible sound.
- Strobe alarm light
- Pre-recorded audio messages
- Auto-tracking
- 2-Way audio
- Micro SD card slot
- IP66 Protection (Indoor/Outdoor)
- Onvif Support (Profile S, Profile G, Profile T)



# Download the Illumivue App

Access, Set-up, and Manage Illumivue surveillance products through your network via iOS, Android or Windows.



Camera						
Sensor	1/2.7" progressive scan, 5.0 megapixel, CMOS					
Lens	2.8~12mm?AF automatic focusing and motorized zoom lens					
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	
	2.8mm	63.0	25.2	12.6	6.3	
	12mm	270.0	108.0	54.0	27.0	
Angle Of View (H)	30.6°~104.1°					
Angle Of View (V)	17.4°~54.9°					
Angle Of View (O)	34.4°~108.3°					
Minimum Illumination	Colour:0.003 lux (F1.6,AGC ON) 0 lux with IR					
IR Range	Up to 50m (164ft) IR range					
IR On/Off Control	Auto/Manual					
WDR	120dB					
Edge Storage	Micro SD, up to 256 GB					
Built-in Mic	Supported					
Built-in Speaker	Supported					
Alarm Light	Supported					
Pan & Tilt						
Pan Range	0° ~345°					
Tilt Range	-10~110°					
Number of Presets	256					



<b>Camera</b>
---------------

<b>Video</b>
--------------

Video Compression	Ultra 265, H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main Profile

<b>Image</b>
--------------

Digital Noise Reduction	2D/3D DNR
Smart IR	Supported
Dewarping	N/A
Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise

<b>General</b>
----------------

Certifications	CE: EN 60950-1 UL: UL60950-1 FCC: FCC Part 15
IP Rating	IP66
Power	DC 12V± 25%, PoE (IEEE802.3 at)
Dimensions (Ø x H)	? 133mm*269.4mm ( ? 5.2” x 10.6” )
Weight	1.13 kg (2.49lb)

