



**ELURA**

Dual 6" 400-Watt Powered Subwoofer

SUBR66-MINI

SKU: 182355    UPC: 81993201364

Introducing the Elura SUBR66-MINI Dual 6" Powered Subwoofer. Unleash the power of immersive, heart-pounding bass with the Elura SUBR66-MINI. This compact yet mighty subwoofer is designed to deliver an exceptional audio experience, boasting a dual-driver configuration that sets it apart from the rest.

At the core of the SUBR66-MINI lies its dual-driver setup. Featuring one active 6" woofer and an additional 6" passive radiator, this subwoofer is engineered to generate deep, resonant bass that you can feel. Whether watching movies, gaming, or enjoying music, the SUBR66-MINI adds a new dimension to any audio, immersing you in the low-frequency rumble that brings the entertainment to life.

Powerful and dynamic, the SUBR66-MINI boasts 400 RMS watts of output. This means it can handle even the most demanding bass lines and explosive sound effects with ease. Whether watching action-packed movies or listening to bass-heavy music genres like EDM or hip-hop, this subwoofer ensures every note is felt, not just heard.

Elegance meets performance with the SUBR66-MINI's high-gloss black finish. Its sleek and stylish design blends seamlessly with any décor, adding a touch of sophistication to any audio setup. Whether it's placed discreetly in a corner or showcased as a centerpiece, this subwoofer not only elevates the audio experience but also enhances the aesthetics of any space.

#### Features

- Elura Red Label
- Dual 6" Hi-Excursion Woofer
- 2" Voice-Coil, Glass Fiber & Paper compound cone with rubber surround
- 400 watt RMS
- High gloss black finish
- Dimensions: 10.7" H x 9" W x 9.5" D
- Versatile placement options

**1-YEAR WARRANTY** - Elura speaker products are guaranteed to meet or exceed the specifications included in this manual and carry with them a 1-year limited warranty under normal conditions of use. This warranty covers free parts and labor on all components with the obligation that Elura will repair or replace any component found defective in materials or workmanship. This warranty does not apply to products that have been abused, incorrectly installed, modified, disassembled and/or repaired by anyone other than Elura or our appointed repair facility.

Amplifier	Digital (Class D) with switching power supply, thermal protection, overload protection, soft clipping short circuit protection, high-efficiency, with low power consumption in standby mode.
Power	400 watt RMS



Input Connections	RCA L/R, LFE Line Level
System Design	Passive Radiator
Woofer	6" Hi-Excursion 2" (50mm) Voice-Coil, Glass Fiber & Paper compound cone with rubber surround
Passive Radiator	6" Glass Fiber & Paper compound cone with rubber surround
Frequency Response	40 - 280Hz Variable
Crossover Control	40 - 120Hz Variable
Controls	Power, Volume, Auto/On, Phase, Crossover Frequency
Safety Rating	TuV
Video-Shielded	No
Dimensions (including feet)	10.7" H x 9" W x 9.5" D (272mm H x 229mm W x 241mm D)
Weight	19.8lbs (8.98kg)
Finish	High Gloss Black