

ELURA



6-Channel 100-Watt Multi-Zone Amplifier

AMP100/6.2

SKU: 188305

Unleash the power of seamless audio distribution with the Elura AMP100/6.2 6-Channel 100-Watt 2U Multi-Zone Amplifier. Engineered for flexibility, this high-performance amplifier offers 6 channels and 3 bridgeable zones, delivering superior audio quality across multiple spaces. Its digital high-power amplification ensures clean, dynamic sound, with 100W at 8 Ω , 120W at 4 Ω , and up to 200W at 8 Ω when bridged. Perfect for multi-room setups, the AMP100/6.2 features global BUS IN and independent channel line inputs, along with SUB OUT connections equipped with variable crossovers for each zone, allowing precise customization for optimal audio performance.

Designed for reliability and convenience, the Elura AMP100/6.2 boasts a 2U rack-mountable chassis with dual cooling fans and a switchable AC power supply for global compatibility. Zone status LEDs and front-panel level controls with a removable security cover simplify monitoring and adjustments. With advanced features like auto-on and 12-volt trigger in/out, BUS output for amplifier linking, and robust short-circuit protection, this D-class amplifier is built for durability and versatility. Whether for home theaters, commercial audio systems, or whole-home sound distribution, the Elura AMP100/6.2 is the ultimate solution for delivering exceptional sound clarity and power to every corner of your space.

Features

- Multi-channel/multi-zone
- Digital high power amplification
- Speaker outputs of 4 Ω and 8 Ω
- Global BUS IN and independent channel line inputs
- All 3 zones bridgeable
- SUB OUT with variable crossover on each zone
- 2U Rack mountable
- Auto-On and Trigger-On
- Front panel level controls with removable security cover
- Zone status LEDs
- BUS output for linking amplifiers
- Short circuit protected
- AC 110/220V 50-60Hz (switchable) power supply system
- 6Ch 100w @ 8ohm, 120w @ 4ohm, 200w @ 8ohm bridged
- D-class with linear high current power supply
- 2U chassis w/ dual fans
- 12volt trigger in/out high 2 global audio inputs and outputs
- Sub outputs on every channel
- Improved slew-rate and dampening factory provides maximum clarity, detail and the ultimate in bass control