



ILLUMIVUE<sup>™</sup> BY MSTR

5MP TVI Turret Camera with NightColor & NightLight - Black

TVI5T-NC-NL-BK

SKU: 187389    UPC: 81993201452

## Illumivue TVI5T-NC-NL 5MP TVI Turret Camera with NightColor & NightLight

### Features

- High quality imaging with 5MP resolution
- TVI/AHD/CVI/CVBS
- Supports IR-cut filter with auto-switch (ICR)
- Smart Dual Light (only TVI)
- Supports 180 horizontal flip, 180 vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages
- Built-in microphone for high quality audio transmission via coaxial cables



## Download the Illumivue App

Access, Set-up, and Manage Illumivue surveillance products through your network via iOS, Android or Windows.



### Camera

Sensor	1/2.7", 5.0 megapixel, CMOS
Lens	2.8mm@F1.6
Angle Of View (H)	110.0°
Angle Of View (V)	57.0°
Angle Of View (D)	130.0°
Minimum Illumination	Colour: 0.0005 lux (F1.6, AGC ON) 0 lux with Light on
IR Range	Up to 40m (131.23ft) IR range
LED On/Off Control	Auto/Manual



Camera	
WDR	DWDR
Built-in Mic	Supported
Built-in Speaker	N/A

Video	
Resolution	5MP@25fps: 2880(H)×1620(V); 5MP@20fps: 2592(H)×1944(V); 5MP@12.5fps: 2592(H)×1944(V) / 4MP: 2560(H)×1440(V) / 1080P: 1920(H)×1080(V)
Frame Rate	TVI: 5MP@20fps (default), 5MP@12.5fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps AHD: 5MP@20fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps CVI: 5MP@25fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps CVBS: PAL, NTSC

Image	
Exposure Mode	Four modes: Global (default), BLC, HLC, DWDR
Day/Night	Three modes: Auto (default), Day, Night
Digital Noise Reduction	2D
Flip	Supports 180°horizontal flip, 180°vertical flip

General	
Certifications	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035); FCC (FCC 47 CFR part15 B)
IP Rating	IP67
Power	DC 12V±25%
Dimensions (Ø x H)	? 110.53 x 97.60mm (?4.3" x 3.8")



Camera	
Weight	0.24kg (0.53lb)